



Product:	<i>PVC 200 C x B Black</i>
Product Construction:	Solid Woven 200 lb rated polyester, Black Standard PVC, Cover by Brushed
Color:	Black
Compound Formulation:	Thermoplastic Std. PVC
Durometer	65 +/- Shore A
Nominal Overall Gauge, inches:	0.203" +/- 10%
mm:	5.2 mm. +/- 10%
Nominal Weight, lbs/ft²:	1.3 lbs/ft ² +/- 10%
kg/m²:	6.3 kg/m ² +/- 10%
Rated Working Tension:	200 lbs/inch / 35 N/mm. @ <2%
Top Cover Surface:	Smooth Cover
Bottom Cover Surface:	Friction
Minimum Pulley Diameter (inches/mm):	4.0 inches / 102 mm.
Temperature Range:	0° to 180° F. / -18° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	N/A
Cover Coefficient of Friction, Steel:	0.8, nominal
Cardboard:	0.5, nominal
Bottom Coefficient of Friction, Steel:	0.6, maximum
Cardboard:	0.4, maximum
Production Width(s):	72"/1829mm.
Typical Applications:	General conveying, slider bed, sorting, material handling, picking, transfer conveyors
Specification Date:	10/29/2015

Note: ICL AMERICA, LTD., provides information, both written and verbal, for its products which it believes to be both accurate and representative of the products themselves. This information is based on laboratory tests, Quality Control Reports, and previous experience with these products. This general information is offered as a service only and is not meant as an expression of warranty or the suitability of the product for a particular application.
 ICL AMERICA, LTD., does not assume any liability whatsoever in regard to use of the product or its fitness for use in a given application.
 The buyer of ICL AMERICA's products must determine for themselves the suitability of such products for a given purpose of the buyer.
 ICL AMERICA, LTD., reserves the right to alter the technical specification of this product without prior notice.