

PRODUCT SPECIFICATION



ICL AMERICA LIMITED

Product:	<i>PVC 200 MOR CT x F White</i>
Product Construction:	Solid Woven 200 lb rated polyester, White MOR PVC, Crescent Top by Friction
Color:	White
Compound Formulation:	Thermoplastic MOR PVC
Durometer	65 +/- Shore A
Nominal Overall Gauge, inches:	0.325" +/- 10%
mm:	8.3 mm. +/- 10%
Nominal Weight, lbs/ft²:	1.3 lbs/ft ² +/- 10%
kg/m²:	6.3 kg/m ² +/- 10%
Rated Working Tension:	200 lbs/inch / 35 N/mm. @ <2%
Top Cover Surface:	Crescent Top
Bottom Cover Surface:	Brushed
Minimum Pulley Diameter (inches/mm):	4.0 inches / 102 mm.
Temperature Range:	0° to 180° F. / -18° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	Meets FDA requirements
Cover Coefficient of Friction, Steel:	1.3, nominal
Cardboard:	0.9, nominal
Bottom Coefficient of Friction, Steel:	0.8, maximum
Cardboard:	0.7, maximum
Production Width(s):	72"/1829mm.
Typical Applications:	Incline food processing in moderate oil and fatty conditions
Specification Date:	10/29/2015

Note: ICL AMERICA, LTD., provides information, both written and verbal, for its products which it believes to be both accurate and representative of the products themselves. This information is based on laboratory tests, Quality Control Reports, and previous experience with these products. This general information is offered as a service only and is not meant as an expression of warranty or the suitability of the product for a particular application. ICL AMERICA, LTD., does not assume any liability whatsoever in regard to use of the product or its fitness for use in a given application. The buyer of ICL AMERICA's products must determine for themselves the suitability of such products for a given purpose of the buyer. ICL AMERICA, LTD., reserves the right to alter the technical specification of this product without prior notice.

Contact: 516-792-3674

sales@iclamerica.com

www.iclamerica.com